



BOLLAX L



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

BOLLAX L 10W

LED BOLLARD LIGHT

- ❑ High Luminous Efficacy - More light output.
- ❑ Corrosion-**resistant** body - Ensures long-lasting durability.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ Quick & easy installation - with accessible mounting design.
- ❑ Consistent Performance & Quality - Delivers stable brightness.




BOL-L-10

Technical			IK08	IP65	UGR <19	CRI ≥80
Light Source			SMD		-	
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt	
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin	
Lifetime			50,000		Hours	
McAdam Binning			3		Step	
Housing						
Body			Aluminium		Die-cast	
Lens / Diffuser			PC Lens & Glass			
Reflector			-			
Mounting			Surface			
Thermal						
Ambient Temperature (Ta)			-20 to 50		°Celsius	
Storage Temperature (Ts)			-20 to 50		°Celsius	
Humidity			10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Tridonic	On/off		
Rated Power	10	Watts		
Input Current (@ 230V)	0.04	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	300	mA		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

D	L	H	Cutout	Weight
-	260	1000	-	- kg

PHOTOMETRIC DETAILS

Beam Angle	105°
------------	------

