



MAGNOR RD



📞 +971 65 260 706 📩 sales-me@hansagreen.com

📍 Hamriyah Free Zone Sharjah, UAE.

MAGNOR RD 03W

LED RECESSED DOWN LIGHT

- **Diffused** Illumination – Soft, uniform, glare-free light.
- Easy installation - **Tool-free** spring-clip installation.
- Long Life: 50,000+ hrs – Minimal maintenance.
- Consistent Performance & Quality - Delivers stable brightness.
- High Luminous Efficacy - More light output.




MNR-RD-03

Technical	IK02	IP20	UGR <19	CRI >80
Light Source	SMD	-	-	-
Luminous Efficacy (subject to a tolerance of ±10%)	100	Lumen / Watt		
Correlated Colour Temperature (CCT)	3000/4000/6500	Kelvin		
Lifetime	50,000	Hours		
McAdam Binning	3	Step		
Housing				
Body	Aluminium	Die-cast		
Lens / Diffuser	PC Diffuser			
Reflector	-			
Mounting	Recessed			
Thermal				
Ambient Temperature (Ta)	-20 to 45	°Celsius		
Storage Temperature (Ts)	-20 to 50	°Celsius		
Humidity	10 to 90	RH(%)		

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF PHASE DIMMING 1-10V DALI	
Control Brand	Hansagreen/Tridonic	On/off
Rated Power	3	Watts
Input Current (@ 230V)	0.013	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hz
Output Current	150	mA
Output Voltage	24 to 42	VDC
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
70Ø	-	30	50Ø	0.05 kg

PHOTOMETRIC DETAILS

Beam Angle	110.3°
------------	--------

