



PACIFIC LX



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

PACIFIC LX 750W

LED FLOOD LIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Efficient Heat Dissipation – Die-cast aluminum housing
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Adjustable Bracket – Easy installation & aiming
- ❑ Consistent Performance & Quality - Delivers stable brightness




PLX-FLD-750

Technical			IK10	IP66	UGR <19	CRI >80
Light Source			SMD		-	
Luminous Efficacy (subject to a tolerance of $\pm 10\%$)			140		Lumen / Watt	
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin	
Lifetime			50,000		Hours	
McAdam Binning			3		Step	
Housing						
Body			Aluminium		Die-cast	
Lens / Diffuser			PC Lens			
Reflector			-			
Mounting			Surface / Pole			
Thermal						
Ambient Temperature (Ta)			-20 to 50		°Celsius	
Storage Temperature (Ts)			-20 to 50		°Celsius	
Humidity			10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF  	
Control Brand	Moso	On/off
Rated Power	750	Watts
Input Current (@ 230V)	3.26	Amps
Input Voltage	100 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	1050	mA
Output Voltage	171-343	VDC
Power Factor	0.9	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
435	595	370	-	14.44 Kg

Bracket Dimensions in mm

L	W	D	Cutout	Weight
45	-	10	-	-

PHOTOMETRIC DETAILS

Beam Angle	55.6°
------------	-------

