



SPLASH RD



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

SPLASH RD 24W

LED INGROUND LIGHT

- ☐ Stainless steel trim corrosion protection
- ☐ IP67 strong water resistance.
- ☐ IK09 drive-over durability
- ☐ Durable toughened glass for safety.
- ☐ Seamless inground installation, no obstacles




BL-24-RD

Technical			IK10	IP67	UGR <19	CRI ≥80
Light Source			SMD		-	
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt	
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin	
Lifetime			50,000		Hours	
McAdam Binning			3		Step	
Housing						
Body			Stainless Steel Trim		Aluminium Die-cast body	
Lens / Diffuser			Toughened Glass			
Reflector			-			
Mounting			Inground recessed			
Thermal						
Ambient Temperature (Ta)			-20 to 50		°Celsius	
Storage Temperature (Ts)			-20 to 50		°Celsius	
Humidity			10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	-			On/off
Rated Power	24			Watts
Input Current (@ 230V)	0.10			Amps
Input Voltage	220 to 240			VAC
Frequency	50 to 60			Hertz
Output Current	600			mA
Output Voltage	24 to 42			VDC
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
200Ø	-	100	187	- kg

PHOTOMETRIC DETAILS

Beam Angle	29°
------------	-----

